



IP66 LED tube with its practical integrated driver for poultry cage applications. This will allow you to achieve considerable savings in terms of energy consumption and maintenance costs.

	23W
Product code	TL6APP-23W-REG-V-RW
Designation	IP66 waterproof LED tube 23W red and white dimmable ROTATING END-CAP = possibility of tube orientation
Structure	Robust molded plastic with polycarbonate lens and polymer cable gland
Fixation and connectors	Fixing grommet and INOX and a wire of 70cm in 2 wires (Phase and Neutral) - Class II
Current flow	Built-in bypass
Dimensions	1 800 mm
Washable	Yes at 1500 psi / 100 bar at 1 meter
LED diode brand	Everlight or JF-LED
Consumption	23W
Light power	2 530 lm
Luminous efficiency	110 lm/W
Variation	Dimmable from 0.2% to 100% on 230V or via 0-10V signal
Color T°	1500°K to 5000°K (red and white)
Color rendering index	≥80
Optical	Clear
Angle of diffusion	220°
% flicker of non-visible light	4%
Glare rate-Standard 12464-1	≤ 23 (Cloakroom, technical room, shop)
IP water protection index	IP 66
IK impact protection class	IK 08
Power factor	0.95
Total harmonic distortion (THD)	<15%
Permissible ambient T°	-20°C / +40°C
Supply voltage / Frequency	175-285 Vac / 50Hz
Lifetime / Warranty	≥50 000h / 5 years
Certifications	 