

Hanging LED tube with its integrated driver ideal for poultry houses, agricultural, commercial, and industrial buildings. This will allow you to achieve considerable savings in terms of energy consumption and maintenance costs. It replaces any light fixture with bulb or fluorescent tube.

	30W
Product code	TL6HT30W85/145V TL6HT30W175/285V
Designation	Waterproof LED Tube 30 Watt double V-shape
Structure	Robust molded plastic with polycarbonate lens and polymer cable gland
Fixation et connectors	Eyelet and INOX fixing with 100cm 2-wire (Phase and Neutral) wire - Class II
Dimensions	6' available 8' and 10' on demand
Washable	with up to 1500 PSI steam pressure at a temperature up to 200° F
LED diode brand	Samsung
Consumption	30W
Light power	3 600 lm
Luminous efficiency	120 lm/W
Dimmable	0,2% to 100%
Color T°	3000K
Color rendering index	≥83
Optical	Clear, Frosted
Beam angle	360°
% flicker of non-visible light	<4%
IP water protection index	IP 67 (NEMA 4X)
IK impact protection class	IK 08
Power factor	0.95
Total harmonic distortion (THD)	<15%
Maximum ambient T°	-20°c / +50°c
Supply voltage / Frequency	85/145V (175/285V on demand) / 50/60Hz
Lifetime / Warranty	≥80 000h / 5 years
Certifications	  

