



IP66 LED tube with its integrated driver, practical for poultry cage applications. This will allow you to achieve considerable savings in terms of energy consumption and maintenance costs.

	<b>30 W</b>
<b>Product code</b>	<b>TL6L30W85/285V</b>
<b>Designation</b>	Linear waterproof LED tube IP66
<b>Structure</b>	Robust molded plastic with polycarbonate optics and polymer cable gland
<b>Dimensions</b>	6'
<b>Washable</b>	with up to 1500 PSI steam pressure at a temperature up to 200° F
<b>LED diode brand</b>	Samsung
<b>Consumption</b>	30W
<b>Light power</b>	3 900 lm
<b>Luminous efficiency</b>	130 lm/W
<b>Dimmable</b>	Non-dimmable
<b>Color T°</b>	6500K
<b>Color rendering index</b>	≥83
<b>Optical</b>	Clear, Frosted
<b>Beam angle</b>	120°
<b>% flicker of non-visible light</b>	<4%
<b>IP water protection index</b>	IP 66
<b>IK impact protection class</b>	IK 05
<b>Power factor</b>	0.95
<b>Total harmonic distortion (THD)</b>	<15%
<b>Maximum ambient T°</b>	-20°c / +50°c
<b>Supply voltage / Frequency</b>	85/285V / 50/60Hz
<b>Lifetime / Warranty</b>	≥80 000h / 5 years
<b>Certifications</b>	