



LED tube FULL SPECTRUM special fattening adapted to several types of breeding (mixed production: chicken / turkey, pork, cattle, etc.). An LED tube with its integrated driver ideal for agricultural building applications. CBM technology can regulate from 0.2% to 100% directly on the power line. It will allow you to make considerable savings both in energy consumption and maintenance costs. It replaces one for one, 36-watt T8 fluorescent tube and 40-watt T12 plus ballast.

	23W
Product code	TL6V23W85/145V-FS TL6V23W175/285V-FS
Designation	V-shape Full Spectrum IP 66 23W
Structure	Robust molded plastic with polycarbonate optics and polymer cable gland
Dimensions	6'
Washable	with up to 1500 PSI steam pressure at a temperature up to 200° F
LED diode brand	Everlight ou JF-LED
Consumption	23W
Light power	2 990 lm
Luminous efficiency	130 lm/W
Dimmable	0,2% to 100%
Color T°	Full Spectrum
Color rendering index	≥85
Optical	Clear
Beam angle	220°
% flicker of non-visible light	<4%
IP water protection index	IP 66
IK impact protection class	IK 08
Power factor	0.95
Total harmonic distortion (THD)	<15%
Maximum ambient T°	-20°c / +50°c
Supply voltage / Frequency	85/145V (175/285V on demand) / 50Hz
Lifetime / Warranty	≥ 80 000 h / 5 years
Certifications	 