



IP66 LED tube with its integrated driver, practical for poultry cage applications. This will allow you to achieve considerable savings in terms of energy consumption and maintenance costs.

	9 W	18 W	30 W
Product code	TL6V9W85/145V TL6V9W175/285V	TL6V18W85/145V TL6V18W175/285V	TL6V30W85/285V
Designation	V-Shape waterproof LED tube		
Structure	Robust molded plastic with polycarbonate optics and polymer cable gland		
Dimensions	6'		
Washable	with up to 1500 PSI steam pressure at a temperature up to 200° F		
LED diode brand	Samsung		
Consumption	9W	18W	30W
Light power	1 170 lm	2 340 lm	3 900 lm
Luminous efficiency	130 lm/W		
Dimmable	0,2% to 100%		Non-dimmable
Color T°	3000K	3000K, 4000K, 6500K	6500K
Color rendering index	≥83		
Optical	Clear		Clear, Frosted
Beam angle	220°		
% flicker of non-visible light	<4%		
IP water protection index	IP 66		
IK impact protection class	IK 08		
Power factor	0.95		
Total harmonic distortion (THD)	<15%		
Maximum ambient T°	-20°c / +50°c		
Supply voltage / Frequency	85/145V (175/285V on demand) / 50/60Hz		85/285V / 50/60Hz
Lifetime / Warranty	≥80 000h / 5 years		
Certifications	 		