


Hanging LED tube with its integrated driver ideal for poultry houses, agricultural, commercial, and industrial buildings. This will allow you to achieve considerable savings in terms of energy consumption and maintenance costs. It replaces any light fixture with bulb or fluorescent tube.



	30W	
Product code	TL4H360-85/145V TL4H360-175/285V	TL6HT30W85/145V TL6HT30W175/285V
Designation	Waterproof LED Tube 30 Watt double V-shape	
Structure	Robust molded plastic with polycarbonate lens and polymer cable gland	
Fixation et connectors	Eyelet and INOX fixing with 100cm 2-wire (Phase and Neutral) wire - Class II	
Dimensions	4' available 5' et 6 on demand	6' available 8' and 10' on demand
Washable	with up to 1500 PSI steam pressure at a temperature up to 200° F	
LED diode brand	Samsung	
Consumption	30W	30W
Light power	3. 900 lm	3 600 lm
Luminous efficiency	130 lm/W	120 lm/W
Dimmable	0,2% to 100%	
Color T°	3000K	
Color rendering index	≥80	≥83
Optical	Frosted	Clear, Frosted
Beam angle	360°	
% flicker of non-visible light	<4%	
IP water protection index	IP66	IP 67 (NEMA 4X)
IK impact protection class	IK 08	
Power factor	0.95	
Total harmonic distortion (THD)	<15%	
Maximum ambient T°	-20°c / +50°c	
Supply voltage / Frequency	85/145V (175/285V on demand) / 50/60Hz	
Lifetime / Warranty	≥80 000h / 5 years	
Certifications	