



The WAL4-45W100/277V-40K wrap-around luminaire features a low profile linear housing with decorative plastic end caps and a white acrylic diffuser for wide, even illumination.

It provides general lighting for residential and light commercial surface mounted applications. Ideal for use in kitchens, offices, utility work areas and stairways. The 4 "fixture includes connection end caps to connect multiple units in a linear fashion. Five year/50,000 hour limited warranty.

	45 W
Product code (dimmmable)	WAL4-45W100/277V-40K
Designation	Linear fixture for residential and light commercial surface mounted applications
Structure	Steel construction with white enamel finish. LED Light Bar
Dimensions and weight	1204mm x 138.1mm x 62mm 1.93kg
LED diode brand	Smilite, SMD 2835
Consumption	45W
Light power	5 310 lm
Luminous efficiency	118 lm/W
Dimmable	Dimmable
Color T°	4 000K
Color rendering index	≥80
Optical	Clear
Beam angle	120°
% flicker of non-visible light	<4%
IP water protection index	IP 40
IK impact protection class	IK 04
Power factor	>0.95
Total harmonic distortion (THD)	<20%
Maximum ambient T°	-30°c / +45°c
Supply voltage / Frequency	100/277V / 50/60Hz
Lifetime / Warranty	≥50 000h / 5 years
Certifications	  