



LED tube with its integrated driver ideal for agricultural building applications. CBM technology can regulate from 0.2% to 100% directly on the power line. It will allow you to make considerable savings both in energy consumption and maintenance costs.

	<b>9 W</b>
<b>Product code</b>	<b>TL4VR9W85/145ED   TL4VR9W175/285ED</b>
<b>Designation</b>	Waterproof LED tube V-shape with rotated END-CAP
<b>Structure</b>	Sturdy molded plastic with polycarbonate lens and polymer cable gland
<b>Current flow</b>	Built-in bypass
<b>Dimensions</b>	4'
<b>Washable</b>	with up to 1500 PSI steam pressure at a temperature up to 200° F
<b>LED diode brand</b>	Samsung
<b>Consumption</b>	9 WATT
<b>Light power</b>	1 170 lm
<b>Luminous efficiency</b>	130 lm/W
<b>Dimmable</b>	0.2% to 100%
<b>Color T°</b>	3000K
<b>Color rendering index</b>	≥83
<b>Optical</b>	Clear or White opal (on demand)
<b>Beam angle</b>	220°
<b>% flicker of non-visible light</b>	<4%
<b>IP water protection index</b>	IP 66
<b>IK impact protection class</b>	IK 08
<b>Power factor</b>	0.95
<b>Total harmonic distortion</b>	<15%
<b>Maximum ambient T°</b>	-20°c / +50°c
<b>Supply voltage / Frequency</b>	85/145V (175/285V on demand) / 50/60Hz
<b>Lifetime / Warranty</b>	≥80 000h / 5 years
<b>Certifications</b>	 