



LED tube with its integrated driver ideal for agricultural building applications. CBM technology can regulate from 0.2% to 100% directly on the power line. It will allow you to make considerable savings both in energy consumption and maintenance costs.

	9 W		
Product code	TL4VR9W85/145ED TL4VR9W175/285ED	TL5VR9W85/145ED TL5VR9W175/285ED	TL6VR9W85/145ED TL6VR9W175/285ED
Designation	Waterproof LED tube V-shape with rotated END-CAP		
Structure	Sturdy molded plastic with polycarbonate lens and polymer cable gland		
Current flow	Built-in bypass		
Dimensions	4'	5'	6'
Washable	with up to 1500 PSI steam pressure at a temperature up to 200° F		
LED diode brand	Samsung		
Consumption	9 WATT		
Light power	1 170 lm		
Luminous efficiency	130 lm/W		
Dimmable	0.2% to 100%		
Color T°	3000K		
Color rendering index	≥83		
Optical	Clear or White opal (on demand)		
Beam angle	220°		
% flicker of non-visible light	<4%		
IP water protection index	IP 66		
IK impact protection class	IK 08		
Power factor	0.95		
Total harmonic distortion	<15%		
Maximum ambient T°	-20°C / +50°C		
Supply voltage / Frequency	85/145V (175/285V on demand) / 50/60Hz		
Lifetime / Warranty	≥80 000h / 5 years		
Certifications	 		