



Great quality IP65 waterproof fixture. Designed to be configured with one, two or three tubes, this product is ideal for medium height ceilings in agricultural, industrial and commercial buildings.

	18 W	18 W	36 W	40 W	60 W
Product code	WP29W85/145ED	WP118W85/145ED	WP218W85/145ED	WP220LED100/277V	WP320LED100/277V
Designation	IP65 waterproof fixture				
	2 x 9W LED tubes	1 x 18W LED tubes	2 x 18W LED tubes	2x20W high lumen LED tubes	3x20W high lumen LED tubes
Structure luminaire	Housing: Compressed fiberglass reinforced polyester (GRP), grey RAL 7035 Diffuser: Injected polycarbonate with UV protection, transparent finish. steel gear tray Latches: plastic or stainless steel				
Dimensions	2' 27 ¾ x 6 7/8 x 4 ½	4' 50 1/8 x 4 x 4 ½	4' 50 1/8 x 6 ¾ x 4 ½		
Washable	with pressure up to 1500 PSI steam at a temperature up to 200° F				
LED diode brand	Philips				
Consumption	18 WATT		36 WATT	40 WATT	60 WATT
Light power	2 340 lm		4 680 lm	5 760 lm	8 640 lm
Luminous efficiency	130 lm/w			160 lm/w	
Dimmable	0.2% to 100%			Non-dimmable	
	3000K, 6500K			5000K, 6000K	
Color rendering index	≥85				
Optical	Clear				
Beam angle	120°				
% flicker of non-visible light	4%				
IP water protection index	IP65				
IK impact protection class	IK08				
Power factor	>0.98				
Total harmonic distortion (THD)	<15%				
Maximum ambient T°	-40°c / +45°c				
Supply voltage / Frequency	85/145V (175/285V on demand) / 50/60Hz			100/277V / 50/60Hz	
Lifetime / Warranty	≥80 000 h / 5 years				
Certifications	CECSP®US				