



Having a clean and elegant design, this LED panel light with a unique internal driver gives a very uniform light output with no dark areas thanks to its rear panel diodes and its diffuser design.

	1 x 4	2 x 2	2 x 4
Product code	PL14-CCT-100/347V	PL22-CCT-100/347V	PL24-CCT-100/347V
Designation	Dimmable LED light panel Fast start, no flickering and noise		
	Tri-Wattage Switch CCT Switch – Back-lit	CCT Switch – Back-lit	
Dimensions	300*1212*30 mm (1'x4')	603*603*30 mm (2'x2')	603*1212*30 mm (2'x4')
LED diode	SMD3030		
Consumption	25 W / 36 W / 40 W	50 W	
Light power	3 125 lm to 5 000 lm	6 250 lm	
Luminous efficiency	125 lm/W		
Dimmable	0.2% to 100%		
Color T°	3500K / 4000K / 5000K - CCT Switch	2700K / 4000K / 6500K - CCT Switch	
Color rendering index	≥80		
Optical	White		
Beam angle	110°	120°	
% flicker of non-visible light	<4%		
IP water protection index	IP 66		
IK impact protection rating	IK 08		
Power factor	>0.9		
Total harmonic distortion (THD)	<15%		
Supply voltage / Frequency	100/347V / 50/60Hz		
Warranty	5 years		
Certifications			