



Hanging LED tube with its integrated driver ideal for applications in poultry houses. It will allow you to make considerable savings both in energy consumption and maintenance costs. It replaces any luminaire with bulb or any fluorescent tube.

	45 W
Product code	TL6H45W85/145V-RW TL6H45W175/285V-RW
Designation	Waterproof LED Tube 6' - 45 Watt red and white
Structure	Robust molded plastic with polycarbonate lens and polymer cable gland
Fixation and connectors	Eyelet and INOX fixing with 100cm 2-wire (Phase and Neutral) wire - Class II
Dimensions	6' available 8' and 10' on demand
Washable	with up to 1500 PSI steam pressure at a temperature up to 200° F
LED diode brand	Samsung
Consumption	45W (30W White / 15W Red)
Light power	3 900 lm / White
Luminous efficiency	130 lm/W / White
Dimmable	0.2% to 100%
Color T°	1500°K to 5000°K (Red and White)
Color rendering index	≥83
Optical	Clear
Beam angle	360°
% flicker of non-visible light	<4%
IP water protection index	IP 67 (NEMA 4X)
IK impact protection class	IK 08
Power factor	0.95
Total harmonic distortion (THD)	<15%
Maximum ambient T°	-20°C / +50°C
Supply voltage / Frequency	85/145V (175/285V on demand) / 50/60Hz
Lifetime / Warranty	≥80 000h / 5 years
Certifications	  