SCR TS Series





An LED system with rubber "T" shaped socket, ideal for applications such as agricultural construction. This IP66 fixture offers excellent heat dissipation. It is built from the best materials. This will allow you to achieve significant savings in terms of energy consumption and maintenance costs.

| | 7 W | 12 W |
|------------------------------|--|------------------|
| Product code (non-dimmable) | SCRTS/7W120V | SCRTS/12W120V |
| Designation | LED bulb IP66 | |
| Structure | 100% pure Lexan "T" shaped rubber with E26 socket | |
| LED diode brand | Samsung | |
| Dimensions | A19 65mm x 120mm | A21 74mm x 124mm |
| Consumption | 7 WATT | 12 WATT |
| Light power | 945 lm | 1 620 lm |
| Luminous efficiency | 135 lumens/watt | |
| Dimmable | No | |
| Color T° | 3000K, 5000K | |
| Color rendering index | ≥80 | |
| Optical | Frosted | |
| Beam angle | 270° | |
| % flicker of invisible light | 4% | |
| IP water protection rating | IP66 | |
| IK impact protection class | IK05 | |
| Power factor | 0.99 | |
| THD | <15% | |
| Maximum ambient T° | -40° c / +50° c | |
| Supply voltage / Frequency | 120V / 50/60Hz | |
| Lifetime / Warranty | ≥ 50 000 h / 5 years | |
| Certifications | CE on one of the contract of t | |