



An LED system with rubber "T" shaped socket, ideal for applications such as agricultural construction. This IP66 fixture offers excellent heat dissipation. It is built from the best materials. This will allow you to achieve significant savings in terms of energy consumption and maintenance costs.

	7 W		12 W	
Product code (dimmable)	SCRTS/7W85/145V SCRTS/7W175/285V		SCRTS/12W85/145V SCRTS/12W175/285V	
Designation	LED bulb IP66			
Structure	100% pure Lexan “T” shaped rubber with E26 socket			
LED diode brand	Samsung			
Dimensions	A19 65mm x 120mm		A21 74mm x 124mm	
Consumption	7 WATT	7 WATT (FS)	12 WATT	12 WATT (FS)
Light power	945 lm	770 lm	1 620 lm	1 320 lm
Luminous efficiency	135 lumens/watt	110 lumens/watt	135 lumens/watt	110 lumens/watt
Dimmable	0.2% to 100%			
Color T°	3000K, 5000K, Full spectrum			
Color rendering index	≥80			
Optical	Frosted			
Beam angle	270°			
% flicker of invisible light	4%			
IP water protection rating	IP66			
IK impact protection class	IK05			
Power factor	0.99			
THD	<15%			
Maximum ambient T°	-40° c / +50° c			
Supply voltage / Frequency	85/145V (175/285V on demand) / 50/60Hz			
Lifetime / Warranty	≥ 50 000 h / 5 years			
Certifications	<div>CEETLUSSP® IntertekCUS</div>			