



An LED system with rubber "T" shaped socket, ideal for applications such as agricultural construction. This IP66 fixture offers excellent heat dissipation. It is built from the best materials. This will allow you to achieve significant savings in terms of energy consumption and maintenance costs.

	9 W	16 W
Product code (dimnable)	SCRTS/9W85/145V SCRTS/9W175/285V	SCRTS/16W85/145V SCRTS/16W175/285V
Designation	LED bulb IP66	
Structure	100% pure Lexan "T" shaped rubber with E26 socket	
LED diode brand	Samsung	
Dimensions	A19 61mm x 115mm	A21 72mm x 124mm
Consumption	9 WATT	16 WATT
Light power	900 lm	1 600 lm
Luminous efficiency	100 lumens/watt	
Dimmable	0.2% to 100%	
Color T°	3000K, 5000K	
Color rendering index	≥80	
Optical	Frosted	
Beam angle	270°	
% flicker of invisible light	4%	
IP water protection rating	IP66	
IK impact protection class	IK05	
Power factor	0.99	
THD	<15%	
Maximum ambient T°	-40° c / +50° c	
Supply voltage / Frequency	85/145V (175/285V on demand) / 50/60Hz	
Lifetime / Warranty	≥ 50 000 h / 5 years	
Certifications		