



Create a true dusk to dawn environment.

The DTD controller allows you to dim CBM lighting products from 0,2% to 100% without flickering. Just like humans, abrupt contrasts in luminosity can add stress and interfere with your animals' well-being. Recreating the natural light cycle is conducive to good animal behavior.

Now with Automatic/Manual knobs, our high precision control allows you to efficiently manage your lighting system. The push buttons with potentiometer knobs enable a swift transition to manual mode.

The DTD controller can be used in Master or Slave mode allowing automated control of lighting according to preset preferences or conditions, therefore offering more flexibility. It is compatible with most centralized systems for an increased optimization of your operations. The DTD-2 version offers the possibility to have both zones operating their own program.

Available in One or Two zone configuration, DTD series offers 10 amps capacity per zone and powered on 120V or 240V.

	DTD-1AB10S	DTD-2AB10S
Line voltage and Frequency	120 / 240 Volts - 50/60 Hz	
Main Fuse	10 amps	
Dimming inputs	1 input 0-10V source	2 inputs 0-10V source
Dimming outputs	1 output 0-10v source	2 outputs 0-10v source
Dimming technology	Transistor	
Power output	1 zone of 10 amps	2 zones of 10 amps
Screen	LCD with pushbuttons	
Bypass switches	Push potentiometer	
Operation mode	Programmable or Slave	
Programing	12 periods of 24 steps	
Minimum level setting method	Internal potentiometer	
Dimensions	290mm x 90mm x 180mm	340mm x 90mm x 180mm
Warranty	2 years warranty on any manufacturing defect	
Origin	Made in Canada	