



SRD-R SWITCH Series

A round LED pendant light adjustable 0-10V allowing a choice of 3 wattages: 100W, 150W or 200W! In 5000K (Day White) also including a 20W Red Night Light.

It will allow you to make considerable savings in both energy consumption and maintenance costs.

	100W/150W/200W + 20W		
SRD200W50KC-R			
Round adjustable LED pendant light with Red Night Light			
Die-cast aluminum housing with high efficiency heat dissipation. Included: 1 m of electrical cable output + fixing eyelet.			
340mm x 150mm (3.4 kgs)			
With pressure up to 105 Bar / With steam at a maximum temperature of 93°C			
2835/3030 - Lm80			
100W	150W	200W	
16 000 lm	24 000 lm	32 000 lm	
160 lm/W			
Dimmable 0-10V			
5000K + Red 630nm (in the center of the suspension)			
≥80			
Clear			
120°			
4%			
IP 66			
IK 08			
>0.9			
<20%			
-40°c / +45°c			
120/240V / 50/60Hz			
7 years			
	Œ		
SRDSUPPORT200W wall mount			
	Die-cast alumincluded With pressure up to 100W 16 000 lm 5000K +	Die-cast aluminum housing with high efficiency heat Included: 1 m of electrical cable output + fixing 340mm x 150mm (3.4 kgs) With pressure up to 105 Bar / With steam at a maximum te 2835/3030 - Lm80 100W 150W 16 000 Im 24 000 Im 160 Im/W Dimmable 0-10V 5000K + Red 630nm (in the center of the suspense of the	







Diagram of the different electrical cables for connection.

